



MAGNUM Basic Steel is a simple and also very robust control unit which is equipped with the energy-efficient Grundfos ALPHA2 L pump with the energy label A. This is also called a modulating pump.

The manifold is hydraulically neutral, this means that the pump of the manifold does not have influence on the primary circuit.

The manifold is pressure tested at 6 bar provided with a press report, clear instruction manual and warranty card.

- The body of the manifold is galvanized and powder coated in black RAL 9011
- Equipped with a thermostat, thermometer and maximum security.
- Standard equipped with an energy-efficient ALPHA2 L pump.
- Double adjustable thermostatic valve groups for MAGNUM actuators.
- Group connections for 3/4 Euro cone.
- Primary connection . "(from 7 groups .")
- Distributor is equipped with fasteners.

Warranty

5 years on the body, 2 years on fittings

Part.no.	Description	Dimensions (LxHxW)
W40001	MAGNUM Basic Steel 1 Ports incl. ALPHA2 L	190 x 390 x 145 mm
W40002	MAGNUM Basic Steel 2 Ports incl. ALPHA2 L	190 x 290 x 145 mm
W40003	MAGNUM Basic Steel 3 Ports incl. ALPHA2 L	245 x 390 x 145 mm
W40004	MAGNUM Basic Steel 4 Ports incl. ALPHA2 L	300 x 390 x 145 mm
W40005	MAGNUM Basic Steel 5 Ports incl. ALPHA2 L	355 x 390 x 145 mm
W40006	MAGNUM Basic Steel 6 Ports incl. ALPHA2 L	410 x 390 x 145 mm
W40007	MAGNUM Basic Steel 7 Ports incl. ALPHA2 L	465 x 390 x 145 mm
W40008	MAGNUM Basic Steel 8 Ports incl. ALPHA2 L	520 x 390 x 145 mm
W40009	MAGNUM Basic Steel 9 Ports incl. ALPHA2 L	575 x 390 x 145 mm
W40010	MAGNUM Basic Steel 10 Ports incl. ALPHA2 L	630 x 390 x 145 mm