



This professional premium MAGNUM control unit is very compact and made of high quality stainless steel type 4301. This allows MAGNUM to give 10 year guarantee on the body of the manifold. The manifold is equipped with a ALPHA2 L pump. Standard with a primary connection above. This pump has a constant pressure, so that it is self-adjusting as there are groups to be closed by a possible after-control (actuator).

The manifold is hydraulically neutral, this means that the pump of the manifold does not have influence on the primary circuit.

This manifold is also available with the pump left or right, primary top or below connection terminal.

The manifold is pressure tested at 6 bar provided with a press report, clear instruction manual and warranty card..

- The body of the manifold is RVS 4301
- Equipped with a thermostat, thermometer, automatic airvent and maximum security.
- Standard equipped with an energy-efficient ALPHA2 L pump.
- Thermostatic valve groups M30X 1.5 for MAGNUM actuators.
- Groups with a professional flow meter with a range of 0-5L / min.
- Group connections for 2/4 Euro cone.
- Primary connection 1/2 (groups from 8 2/4)
- Manifold is equipped with fasteners.

Part.no.	Description	Dimensions (LxHxW)
W30001	1 Ports incl. ALPHA2 L	395 x 200 x 150 mm
W30002	2 Ports incl. ALPHA2 L	395 x 200 x 150 mm
W30003	3 Ports incl. ALPHA2 L	395 x 200 x 150 mm
W30004	4 Ports incl. ALPHA2 L	450 x 200 x 150 mm
W30005	5 Ports incl. ALPHA2 L	505 x 200 x 150 mm
W30006	6 Ports incl. ALPHA2 L	560 x 200 x 150 mm
W30007	7 Ports incl. ALPHA2 L	615 x 200 x 150 mm
W30008	8 Ports incl. ALPHA2 L	670 x 200 x 150 mm
W30009	9 Ports incl. ALPHA2 L	725 x 200 x 150 mm
W300010	10 Ports incl. ALPHA2 L	780 x 200 x 150 mm
W300011	11 Ports incl. ALPHA2 L	835 x 200 x 150 mm
W300012	12 Ports incl. ALPHA2 L	890 x 200 x 150 mm
W300013	13 Ports incl. ALPHA2 L	945 x 200 x 150 mm
W300014	14 Ports incl. ALPHA2 L	1000 x 200 x 150 mm
W300015	15 Ports incl. ALPHA2 L	1050 x 200 x 150 mm